



USB Ranger® 2211

Extends USB 2.0 over Cat 5 with Flexible Power

The USB Ranger® 2211 extends High-Speed USB 2.0 connections beyond the desktop up to 100 meters with the option to power either the local extender or remote extender.

icron

4664 Lougheed Hwy.
Suite 221
Burnaby, BC,
V5C 5T5, Canada

www.icron.com
sales@icron.com
+1 604 638 3920

HETEC Datensysteme GmbH
Franz-Josef-Delonge-Str. 5
D-81249 München
Tel.: +49 (0)89 - 89 43 67 - 12
Email: info@hetec.de
web: https://www.hetec.de



Local Extender




Remote Extender

USB Ranger® 2211 Features

The USB Ranger® 2211 uses patented technology ideal for extending USB peripherals including: keyboards, mice, interactive white boards, flash drives, hard drives, audio devices, USB 2.0 web cameras and any other USB 2.0 or 1.1 device.

- Ability to provide power at either the local extender or remote extender. Power is delivered over the Cat 5 cable
- Extends USB 2.0 high-speed and USB 1.1 (low-speed, full-speed) devices
- Operates with USB 1.1 and USB 2.0 hosts
- Supports all USB devices up to 480Mbps
- True plug and play. No drivers required
- Supports all major operating systems: Windows®, Mac OS X®, and Linux®
- Uses a standard solid core Cat 5 cable for easy installation
- Number of devices can be increased using additional USB hubs



Specifications subject to
change without notification.
©2012
Icron Technologies Corp.
#90-00949-A01

EXTREME
USB

Applications

- Interactive White Board
- Corporate Board Room: USB Device Extension
- KVM Extension: Keyboard and Mouse
- Industrial Control



Specifications subject to change without notification.
©2012
Icron Technologies Corp.
#90-00949-A01

PERFORMANCE

Reach:	330 feet (100 meters)
Power:	24V DC @ 1A (24W)

LOCAL EXTENDER

LEX unit USB Connector:	1 x USB Type B Receptacle
LEX unit Link Connector:	1 x RJ45
Dimensions:	3.35" x 1.10" x 2.25" (85mm x 28mm x 57mm)
Mounting:	2 mounting slots on each side

REMOTE EXTENDER

REX unit USB Connector:	1 x USB Type A Receptacle
REX unit Link Connector:	1 x RJ45
Maximum current available at REX:	500mA
Dimensions:	3.35" x 1.10" x 2.25" (85mm x 28mm x 57mm)
Mounting:	2 mounting slots on each side

ENVIRONMENTAL

Operating Temperature:	32°F to 122°F (0°C to 50°C)
------------------------	-----------------------------

CERTIFICATIONS

EMC:	FCC (Class A), CE (Class A)
Compliance:	RoHS
Flammability:	V-0



Ordering Information

The USB Ranger® 2211 system includes a Local Extender (LEX) module, a Remote Extender (REX) module, a USB Cable, and a Quick Start Guide. The extenders are covered by a one year warranty.

For more information, email sales@icron.com or call +1 604 638 3920.

PART NUMBER	NAME	DESCRIPTION
00-00315	USB Ranger® 2211	Flexible Power 1-Port Cat 5 USB 2.0 Extender, 100-240V Power Adapter, NA plug
00-00316	USB Ranger® 2211	Flexible Power 1-Port Cat 5 USB 2.0 Extender, 100-240V Power Adapter, EU plug
00-00317	USB Ranger® 2211	Flexible Power 1-Port Cat 5 USB 2.0 Extender, 100-240V Power Adapter, UK plug
00-00318	USB Ranger® 2211	Flexible Power 1-Port Cat 5 USB 2.0 Extender, 100-240V Power Adapter, AUS plug